

TREND MICRO SOFTWARE APPLIANCE SUPPORT

What Trend Micro solutions support Software Appliance deployments?

The following solutions support the software appliance form factor, and the subsequent hardware platforms

Reference	Product
IWSVA	InterScan Web Security Virtual Appliance
IMSVa	InterScan Messaging Security Virtual Appliance
ARM	Advanced Reporting and Management (for InterScan Web Security v5.x)

Bare Metal Server Platform Matrix

Platform	Trend Micro Solution				
	IWSVA		IMSVa	IMSVa	ARM
Version	v6.0	v5.6	V8.x	v7.x	v1.6
Build	1214	1364	1304	1170	1068
Dell					
R900					
R720					
R710					
R610					
R420					
R410					
R300					
R210 II					
R200					
2950 Series II/III					
1950 Series II/III					
1850 Series II					
Hitachi					
BladeSymphony 1000					
HP					
BL 460 C Generation 1					
DL 360 G7					
DL 360 G6					
DL 380 G7					
DL 380 G6					
DL 380 G5					
DL 385 G6					

Certified by Trend Micro Platforms

Independent Hardware Platforms supporting Trend Micro Software Appliance Deployments

DL 385 G2					
DL 350 G5					
DL 388p G8					
DL 380p G8					

Bare Metal Server Platform Matrix

Platform	Trend Micro Solution				
	IWSVA		IMSV A	IMSV A	ARM
	Version	v6.0	v5.6	V8.x	v7.x
Build	1214	1364	1304	1170	1068
IBM					
Systems x3550					
NEC					
Express5800 R120a-1					
Express5800 R120RH-1					
Resilience					
ATL 1012					
Sun					
Sunfire X4450					
SuperMicro					
Superserver 1026T					
Superserver 5016T					

Bare Metal Server Specifications

	CPU	Memory	Hard Drive	HD Controller	NIC
Dell PowerEdge					
R900	2 x Intel X7460 Xeon, Six Cores, 2.67GHz, 16MB Cache, 1066Mhz FSB	32GB Memory, 16X2GB, 667MHz	300GB 15K RPM Serial-Attach SCSI 3Gbps 3.5-in HotPlug Hard Drive		
R720	Intel® Xeon® E5-2603 1.80GHz, 10M Cache, 6.4GT/s QPI, No Turbo, 4C, 80W, Max Mem 1066MHz	2-16GB Memory	500GB 7.2K RPM SATA 3Gbps 3.5in Hot-plug Hard Drive		
R710	2 x Intel Quad Core E5570 Xeon CPU, 2.93GHz	24GB Memory (6x4GB), 1333MHz, Dual Ranked U 1 DIMMs for 2 Processors	4*300GB SAS 10000 RPM	PERC 6/I, Integrated Controller Card	Integrated 2 x Two Broadcom 5709C dual-port Giga –bit Ethernet with TOE enabled
R710	2 x Intell 6-Core X5670 Xeonl CPU, 2.93Ghz	24GB Memory, 1333Mhz Dual Ranked RDIMM for 2 Processors	2*250GB SATA 7.2k 3.5"	PERC 6/I, Integrated Controller Card	Integrated 2 x Two Broadcom 5709C dual-port Giga –bit Ethernet with TOE enabled

Certified by Trend Micro Platforms

Independent Hardware Platforms supporting Trend Micro Software Appliance Deployments

R610	2 x Intel Quad Core E5506 Xeon CPU, (2.13GHz)	8GB Memory (4x2GB), 1333MHz, Dual Ranked U 1 DIMMs for 2 Processors	2*160GB SAS 7200 RPM	PERC 6/I, Integrated Controller Card	Integrated 2 x Two Broadcom 5709C dual-port Giga-bit Ethernet with TOE enabled
R420	Intel Xeon processor E5-2400 product family	Up to 384GB (12 DIMM slots): 2GB/4GB/8GB/16GB/32GB DDR3 up to 1600MT/s	Up to 16TB		
R410	Intel Quad Core E5504 Xeon CPU, (2.0GHz)	4GB Memory (4x1GB), 1333MHz, Single Ranked U 1 DIMMs for 1 Processor	2*160GB SATA 7200 RPM	SAS 6/iR Controller Card	Integrated Broadcom 5716 dual-port Giga-bit Ethernet with TOE enabled
R300	Intel Quad Core Xeon Pro L5410 CPU (2.33GHz)	4GB Memory (2x2GB) DDR-2 667MHz ECC 2R	Western Digital 500GB SAS	PERC 6/I, Integrated Controller Card	Integrated 2 * Two Broadcom 5722 dual-port Giga-bit Ethernet
R210 II	Intel Quad Core Xeon Processor E3-1220 (3.1GHz)	8 GB	500GB SATA 7200 RPM		
R200	Intel Quad Core Xeon X3360, 2.83GHz, 2x6MB Cache, 1333MHz FSB	4 GB	2*250GB 7.2K RPM SATA 3Gbps 3.5in Cabled	SATA/SAS Controller	Dual GB
2950 Series II/III	Intel Quad Core Xeon X5355 (2.66GHz) OR/Intel Quad Core Xeon X5460 (3.16GHz)	8 GB	300GB 10K RPM Serial-Attach SCSI 3Gbps 3.5-in HotPlug HardDrive (341-3032) OR/ 200GB 15K RPM		
1950 Series II/III	Intel Dual Core Xeon 5160 (3.00GHz) OR/Intel Quad Core Xeon E5410 (2.33GHz)	8 GB	500GB 7.2K RPM Universal SATA 3Gbps 3.5-in HotPlug Hard Drive (341-4157)		
1850 Series II	Intel Dual Xeon (3.0GHz)	2 GB	146GB 10K RPM SCSI U320		
	CPU	Memory	Hard Drive	HD Controller	NIC
Hitachi					
BladeSymphony 1000	Intel Xeon E5430 2.66GHz, 4 core, 2 socket - LPAR (Virtage) allocated CPU : vCPU = 2core, occupied)	16GB RAM - LPAR (Virtage) allocated memory size : vMemory = 8192MB - HDD: SAN Storage	Hitachi AMS2300 130GB (RAID1) - HBA Driver : Integrated FC switch module (driver version - 4.5.12.736)		1Gbps (100/1000)
	CPU	Memory	Hard Drive	HD Controller	NIC
HP Proliant					
DL 360 G7	Intel Xeon X5650	24GB	8 x HP 300GB 6G 10K RPM SFF SAS (2.5")	HP Smart Array P410i controller	HP NC382i Dual Port Multifunction Gigabit Adapter
DL 360 G6	Intel Xeon E5540 / X5560 2.53 GHz / 2.8 GHz	6GB /12GB	HP 146GB 3G SAS 10K SFF DP ENT HDD	HP Smart Array P410i/256MB Controller	HP NC382i Dual Port Multifunction Gigabit Adapter
DL 380 G7	Intel Xeon X5650 2.55 Ghz	10GB	HP 146GB SAS 10K Dual Port HDD	HP Smart Array P410i/1G FBWC	HP NC382i Dual Port Multifunction Gigabit Adapter

Certified by Trend Micro Platforms

Independent Hardware Platforms supporting Trend Micro Software Appliance Deployments

DL 380 G6	Intel Quad Core Xeon E5540 2.53 GHz	8GB	HP 146GB SAS 15K RPM (2.5)	HP Smart Array P410i	HP NC382i Dual Port Multifunction Gigabit Adapter
DL 380 G5	Intel Quad Core Xeon E5420 (2.50 GHz)	4GB	2 x HP 146GB SFF SAS 10K RPM (2.5")		
DL 380 G5	Intel Dual Quad Core XEON E5345 2.33Ghz	4GB	HP 300GB DG300FARVV (2x RAID1) SAS RAID	HP Smart Array P400/512	1Gpbs HP (Broadcom) NetXtreme II BCM5708
DL 385 G2	AMD Dual Core Opteron 2220	2GB	2 x HP 146GB SFF SAS 10K RPM (2.5")		
DL 385 G6	AMD Opteron Six Core 2.4GHz	8GB	HP 72GB 6G SAS 15K RPM (2.5)	HP Smart Array P410	HP NC382i Dual Port Multifunction Gigabit Adapter
BL 460 C Generation 1	Intel Xeon Quad E 5440 2.83 GHz Intel Xeon Dual core 2.66 GHz	4GB	HP 2 x 72GB	HP SmartArray E200i	10/100/1000 Mbps Broadcom NetXtreme II BCM 5708 S
DL388p Gen8	Intel® Xeon® E5-2600 product family 2.4GHz	4GB		HP Smart Array P420i/ZM (RAID 0/1/1+0)	1Gb 331FLR Ethernet Adapter 4 Ports per controller or 10Gb 530FLR-SFP+ Ethernet
DL380p Gen8	2 x Intel® Xeon® E5-2665 (8 core, 2.4 GHz, 20MB, 115W)	32GB (4x8GB) RDIMM		Smart Array P420i/2GB FBWC	10Gb 530FLR-SFP+ Ethernet Adapter 2 Ports per controller
IBM					
Systems x3550	Systems x3550	Systems x3550	Systems x3550	Systems x3550	Systems x3550
NEC					
Express5800 R120a-1	Intel Xeon 5550 2.66GHz 4 core processor	16 GB DDR3 DIMM		SATA/SAS Controller	2x 1000BASE-T + 1x 100BASE-TX (Management Port)
Express5800 R120RH-1	Intel Xeon processor E5420 (2.50GHz/1333MHz FSB/2 x 6M L2 Cache)	48 GB (12 x 4GB) Maximum	3.5" SAS: 1.35TB (3 x 450GB) / 3.5" SATA: 3TB (3 x 1TB) / 2.5" SAS: 879GB (6 x 146.5GB) Maximum		
	CPU	Memory	Hard Drive	HD Controller	NIC
Resilience					
ATL 1012	Intel Core 2 DUO E8400 3GHz	4GB	Western Digital 250GB SATA WD2500	Intel PXE 2.1 v1.3	10/100/1000 Mbps Intel
	CPU	Memory	Hard Drive	HD Controller	NIC
Sun					
Sunfire X4450	4 Quad Core Intel Xeon L7345, 1.86 GHz, 1066MHz FSB	8 GB (8 x 1GB DIMMs) Fully Buffered ECC	1168 GB (8 x 146 GB) 10K RPM SAS Disks		
	CPU	Memory	Hard Drive	HD Controller	NIC
SuperMicro					
Superserver 1026T	2 Intel Nehalem E5520 2.26GHz	8 GB	2 x 500 GB	8-port PCI-E SAS	Intel Dual Port
Superserver 5016T	1 Intel Nehalem E5520 2.26GHz	4 GB	1 x 500 GB	SATA 3Gbps	Intel Dual Port

Specialty Server Platform Matrix

Platform	Trend Micro Solution				
	IWSVA		IMSVA	IMSVA	ARM
	Version	v6.0	v5.6	V8.x	v7.x
Build	1214	1364	1304	1170	1068
NEC					
Express5800 R320a-M4 (VMware Model with vSphere 4)					
Express5800 R320a-E4 (VMware Model with vSphere 4)					

Specialty Server Specifications

NEC					
R320a-M4 (VMware Model with vSphere 4)	2 x Intel Xeon X5570 2.93GHz 4 core processor	16G DDR3-1066 DIMM with ECC	3.5" SAS (4 x 73GB)		2x 1000BASE-T + 1x 100BASE-TX (Management Port)
R320a-E4 (VMware Model with vSphere 4)	2 x Intel Xeon E5504 2.0GHz 4 core processor	12G DDR3-1066 DIMM with ECC	3.5" SAS (2 x 73GB)		2x 1000BASE-T + 1x 100BASE-TX (Management Port)

Encryption Acceleration Card Matrix

Product	Hardware Acceleration Card Model
IWSVA v5.6+	Silicom PESC61 (PCI-E)
IWSVA v5.6+	Silicom PESC62 (PCI-E)
IWSVA v5.6+	Silicom PESC51 (PCI-X)
IWSVA v5.6+	Silicom PXSC10 (PCI-X)

Failover Network Card Matrix

Product	Failover NIC Card Model
IWSVA v5.6+	Silicom PXG2BPFIL-SD (Dual Port Fiber (SX) Gigabit PCI-X)
IWSVA v5.6+	Silicom PXG2BPISD (Dual Port Copper Gigabit PCI-X)
IWSVA v5.6+	Silicom PEG2BPFID (Dual Port Fiber (SX) Gigabit PCI-Express)
IWSVA v5.6+	Silicom PEG2BPIC (Dual Port Copper Gigabit Ethernet PCI-Express)
IWSVA v5.6+	Silicom PE2G4BPI35-SD-OU-ROHS (Quad Port Copper Gigabit Ethernet PCI-Express Gen-2)
IWSVA v5.6+	Silicom PEG2BPI6-SD-OU-ROHS (Dual Port Copper Gigabit Ethernet PCI-Express)
IWSVA v5.6+	Silicom PEG2BPFI6-SD-OU-ROHS (Dual Port Fiber PCI-Express)
IWSVA v5.6+	Silicom PEG2BPFI6-LX-SD-OU-ROHS (Dual Port Fiber (LX) PCI-Express)